

# TECHNICAL SHEET ROOFING GAS TORCH

MODEL: FK972



Kind of handgrip

- ☐ NORMAL  
☒ WITH REGULATION TRIGGER

PILOT FLAME

Kind of gas

L.P.G G30 - G31

Admitted pression

1÷7 BAR

Advised pression

2÷5 BAR

Diameter of the burner TURBO

60 mm

Injector (hole diameter)

1.5 mm

Total lenght

1000 mm

Consumption per hour

5.3 Kg a 3 BAR

Power

75 kW

Nominal weight

0.870 Kg

Kind of ignition

MANUAL IGNITION

Plastic component: Fireproof MA 20% GLASS FIBER

Chromium plating made in Italy by certified Company:



**ALL THE PIECES ARE INDIVIDUALLY CHECKED WITH LPG - NOMINAL PRESSION 4 BAR**  
**THE PRODUCT IS HOMOLOGATED DVGW - HOMOLOGATION N. DG-2212M0077**

Rubber weight

0.126 Kg/mt +/- 0.008 Kg/mt

Lenght of the rubber

5 mt

Pression exercise rubber continual use

0 - 20 BAR

Bang pression

> 60 BAR

Temperature range

-20 +70 C°

Expiry of the rubber starting from the date of production

5 years

THE HOSE IS MADE ACCORDING TO THE REGULATION EN ISO 3821: DECLARATION APPROVAL TYPE N. S1498 IMQ

Packaging:  
cardboard  
display with  
use instruction  
& maintenance

