



TECHNICAL DATASHEET - HEATING TORCH

MOD.: FKB412 HEATING TORCH KIT WITH GAS HOSE



Handling type

Gas category

Pressure range

Nominal pressure range

Turbo Burner Ø

Injector (Ø hole)

Total length

Consume/H

Power

Nominal net weight

Ignition:

WITH REGULATION TRIGGER

L.P.G

1÷7 BAR

2÷5 BAR

60 mm

1.5 mm

900 mm

5.3 Kg a 3 BAR

80 kW

0.825 Kg

> 30 BAR

automatic piezoelettric

Chromo treatment by certificated manufacturers



Brust pressure





THE HOSE IS IN CONFORMITY WITH EUROPEAN NORM UNI EN 7140 PVC

Rubber weight 0.106 Kg/mt +/- 0.008 Kg/mt

Rubber hose length 5 mt

Nominal pressure range 0 - 10 BAR

Temperature range - 15° / + 50° C

Expiry of the rubber starting from the date of production 5 years



INTEGRATED FIXING WRENCHES

ALL PCS ARE INDIVIDUALLY TESTED WITH LPG - PRESSURE 4 BAR DVGW HOMOLOGATION N. DG-2212M0077









Packaging in cardboard display with use and maintenance instructions.